

TSB # 756-0038
Prince Castle
355 East Kehoe Blvd
Carol Stream, IL 60188
04/20/2017



Dear Customer,

In a going effort to ensure quality on our Genuine OEM Equipment we are Issuing a TSB for our SKMCD1P/C1. This TSB includes new updated wiring instructions for the replacement solenoid kit (OEM Kit Part # 10327-59). Please follow the new updated wiring instructions. **If failure to follow new wiring instructions any damage to the unit will not be covered under warranty.**

Common Symptoms:

- Solenoid Immediately shorts out upon install
- Solenoid does not cycle

Procedure:

- Follow new wiring instructions on page 2 (OEM Document Part # 41002).

Sincerely,

A handwritten signature in black ink, appearing to read "Paul Svenningsen".

Paul Svenningsen

Technical Service Manager U.S.

TSB # 756-0038
Prince Castle
355 East Kehoe Blvd
Carol Stream, IL 60188
04/20/2017



SKMCD1P/C1 SOLENOID WIRING INSTRUCTIONS

Wiring Instructions Below

- Cut the original blue wire connector and attach the spare connector that is provided in the solenoid kit. Place blue wire from solenoid into the NO4 position on the micro switch (NC1 is open).
- Piggy-back the spare black wire in the solenoid kit with the red solenoid wire and insert into the NO3 position on the micro switch (NC2 is open). The other end of the black wire will go to J8 on the board.
- Connect the black solenoid wire to J10 on the board.

CONTACT INFORMATION

Silver King Support Hot Line
1-844-233-5598 Option 2
silverkinghelp@3wire.com

