

CBT & IRT Horizontal Toaster IRT-Series CBT-Series

Specification Sheet



Features

- Toast core buns and breakfast items simultaneously
- Adjustible compression, speed, and temperature controls
- Stainless steel belt for long term reliability
- Minimal low cost consumables
- Sliding belt drawer for easy cleaning and maintenance
- Modular design for rapid servicing and troubleshooting

- Heated landing zones for core buns
- Gold quality toasting at only 455° (vs. over 550°)
- Breakfast items are fed into UHC tray to minimize product handling
- Dual sided club toasting
- Compatible with single and three phase wiring to eliminate in-store electrical wiring
- Low energy consumption with high bun temperatures





CBT & IRT Horizontal Toaster IRT-Series CBT-Series

Specification Sheet





Technical Specification

Product Category	IRT Series	CBT Series
Product Dimensions	33.3"W x 8.95"H x 16.38"D (84.62)cm x (22.72)cm x (41.61)cm	33.36°W x 10.14°H x 16.11°D (84.74)cm x (25.74)cm x (40.92)cm
Shipping Weight lbs (kg)	122 lbs (55.33)kg	200lbs (90.71)kg
Shipping Volume Cubic Dimensions	11.39 (0.32)	13.0 (0.36)
Certifications	Intertek 3183199 Conforme to ANSIAUL 197 CAL Lister Concentration No. 109	Kenter Ke

Model Number	Description	
IRT-SB-NA-1PS	Infrared Toaster, North American version, single phase plug, 200-240v, 50/60hz, .15.5-17.75amps, Phase-1	
IRT-SB-NA-3PS	Infrared Toaster, North American version, 3 phase plug, 200-240v, 50/60hz, .15.5-17.75amps, Phase-3	
CBT-SB-NA-1PS	Core Bun Toaster, North American version, single phase plug, 200-240v, 50/60hz, .23.5-26.2amps, Phase-1	

To learn more about CBT & IRT Horizontal Toaster, visit princecastle.com

